

SPECIFICATIONS

SUPER CARRY Truck

DIMENSIONS		
Overall length	mm (in.)	3,235(127.3)
Overall width	mm (in.)	1,395(54.9)
Overall height	mm (in.)	1,765(69.5)
Load deck length	mm (in.)	1,940(76.4)
width	mm (in.)	1,320(52.0)
height	mm (in.)	290(11.4)
Wheelbase	mm (in.)	1,840(72.4)
Tread Front	mm (in.)	1,205(47.4)
Rear	mm (in.)	1,200(47.2)
Minimum turning Radius	m (ft.)	4.1(13.5)
WEIGHT		
Curb weight	kg. (lbs)	675(1,488)
Gross vehicle weight	kg. (lbs)	1,410(3,102)
Seating Capacity	Persons	2
ENGINE		
Type	F10A 4-Stroke Cycle, Water Cooled, SOHC	
Number of Cylinders	4	
Piston displacement	cc (cu. in.)	970(59.2)
Bore x stroke	mm (in.)	65.5 x 72.0 (2.58 x 2.83)
Maximum output [EEC net]	kW (Hp)/rpm	33.0(44)/5,300
Maximum torque [EEC net]	Nm (kg-m, lb-ft)/rpm	75.0(7.6, 55.3)/3,200
Fuel tank capacity	liter (US/Imp gal)	36(9.5/7.9)
TRANSMISSION		
Type	5 forward all synchromesh, 1 reverse	
Gear	1st	3.652
	2nd	1.947
	3rd	1.423
	4th	1.000
	5th	0.795
	Reverse	3.466
Final gear ratio	5.125	
CHASSIS		
Suspension	Front	Strut, coil spring
	Rear	Rigid axle, leaf spring
Brakes	Front	Disk
	Rear	leading and trailing
Tyres	5.00-12	

reverse the right to change specifications without prior notice