FLEXIDRIVE™

Tube cleaners and accessories

FLEXIDRIVE™

ELECTRIC POWERED WET & DRY TUBE CLEANER

Model	Type	Motor HP (kW)	Power	Speed	Recommended Shaft Core Diameter/Length
FDM-D-2-1PH	Dry	2.0 (1.5 kW)	1 Phase	1,500 rpm	12 mm, Max 75 ft.
FDM-D-2-3PH	Dry	2.0 (1.5 kW)	3 Phase	1,500 rpm	12 mm, Max 75 ft.
FDM-D-3-3PH	Dry	3.0 (2.2 kW)	3 Phase	3,000 rpm	12 mm, Max 100 ft.
FDM-WD-2-1PH	Wet/Dry	2.0 (1.5 kW)	1 Phase	1,500 rpm	12 mm, Max 75 ft.
FDM-WD-2-3PH	Wet/Dry	2.0 (1.5 kW)	3 Phase	1,500 rpm	12 mm, Max 75 ft.
FDM-WD-3-3PH	Wet/Dry	3.0 (2.2 kW)	3 Phase	3,000 rpm	12 mm, Max 100 ft.

FLEXIDRIVE™

AIR POWERED WET & DRY TUBE CLEANER

Model	Flexible Shaft Speed	Air Motor Power	Air requirements
AWP100X	Variable 500-3,000 rpm	1.8 HP Max .	100 PSI @ 70 CFM Output torque: 46 lb-in @ 2,500 rpm
AWP100XX	Variable 500-3,000 rpm	4 HP Max.	100 PSI @ 130 CFM Output torque: 82 lb-in @ 3,000 rpm

FLEXIDRIVE™

FLEXIBLE SHAFT & ACCESSORIES

- Condenser tube brush (bronze, steel, nylon)
- Turk brush
- Circular Brush
- Double cone cutter
- Tapered Cutter
- Flexible Tool Holder
- Universal Joint
- Single Cone Cutter + Universal Joint
- Disc Cone Cutter
- Rotary Cutter
- Pivoted arm cutter
- Galvanize steel for dry cleaning
- Nylon for wet cleaning